

(12) UK Patent Application (19) GB (11) 2 339 994 (13) A

(43) Date of A Publication 09.02.2000

(21) Application No 9816180.7

(22) Date of Filing 25.07.1998

(71) Applicant(s)

Motorola Limited
(Incorporated in the United Kingdom)
Jays Close, Viables Industrial Estate, BASINGSTOKE,
Hampshire, RG22 4PD, United Kingdom

(72) Inventor(s)

Anthony John Wray
Timothy Simon Klein

(74) Agent and/or Address for Service

Marc Morgan
Motorola Limited, European Intellectual Property
Department, Midpoint, Alencon Link, BASINGSTOKE,
Hampshire, RG21 7PL, United Kingdom

(51) INT CL⁷

H04Q 7/38

(52) UK CL (Edition R)

H4L LDSWX L1H10

(56) Documents Cited

GB 2285900 A GB 2281470 A

(58) Field of Search

UK CL (Edition P) H4L LDLX LDSU
INT CL⁶ H04B 7/26 , H04Q 7/32 7/38
On-Line - WPI

(54) Abstract Title

Collision avoidance by restricting channel access requests according to RSSI

(57) A radio communication system broadcasts a signal (AACH, fig.3) to a plurality of portable and/or mobile radio units 10-20 which defines a minimum received signal strength which a radio unit must receive before it is permitted to make a request for access to the base station 1. The defined minimum value may be varied. Alternatively, the broadcast signal (AACH) may provide a threshold minimum value which each radio unit uses to decide which of two sub groups it belongs to, depending on whether its RSSI is above or below the threshold. The two sub-groups use two different sub-sets of access request time slots for making access requests to the radio communication system. Both arrangements lead to maximising the channel efficiency of the radio communication system. The first restricts the number of radio units which can make access requests. The second allows substantial equalisation of the proportions of access request time slots in which requests collide in each of the two sub-sets of access request time-slots. Suitable for use in a TETRA system.




FIG.2

GB 2 339 994 A